

THREE-PHASE-ASYNCHRONOUS-MOTOR E3-ASA 200 LB 4

IE3UM20L4200

General data

Type of motor	3~ explosion proof
Type designation	E3-ASA
Frame size	200
Mounting	B3
Frame execution	LB
Frame material	Grauguß
Insulationclass	F/F
Terminal box location	top DE
Terminal box orientation	cable gland to the right side
Weight (kg)	368
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to noise level	IEC 60034 -1, EN 60079-0/-1 IEC 60034-9

Influential factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Electrical specification

Power 1 50Hz (kW)	30
Power 1 60Hz (kW)	34,5
Frequency (Hz)	50/60
Voltage 50Hz (V)	400/690
Voltage 60Hz (V)	460/-
Voltage tolerance	+/-5%
Connection	Δ/Y
Poles	4
Efficiency 100% 50Hz (%)	93,6
Efficiency 75% 50Hz (%)	93,4
Efficiency 50% 50Hz (%)	91,8
Efficiency 100% 60Hz (%)	94,5
Efficiency 75% 60Hz (%)	93,5
Efficiency 50% 60Hz (%)	91,9
Power factor	0,79
Starting current factor (Ia/In)	8,7
Starting torque factor (Ma/Mn)	2,7
Breakdown torque (Mk/Mn)	3,0
Rated current 50Hz (A)	59,60/34,45
Rated current 60Hz (A)	58,00
Eff.Cl.50Hz	IE3
Eff.Cl.60Hz	IE3

Mechanical data

Torque (Nm)	192,00/184,89
Rotation speed (1/min)	1485/1782
Bearing DE	
Bearing NDE	
Mounting of bearing DE	fixed bearing
Mounting of bearing NDE	loose bearing
Bearing lifetime (h)	20000
Moment of inertia (kgm ²)	0,31241

Motor properties

Color	RAL7030
Paint surface	matt
Protection class	IP55
Cable gland size (cable connection)	2xM50x1,5
Cable gland size (option)	M20x1,5
Cable gland type	Atex
Shaft end (mm)	55 x 110
Shaft material	C45
Specification NDE	Metal fan

Additional option

Protection winding	PTC 130°C
Atex	II 2G Ex db eb IIC T4 Gb

Dimension drawings
Three-Phase-Asynchronous-
Motor E3-ASA 200 LB 4
IE3UM20L4200

ac motoren