

THREE-PHASE-ASYNCHRONOUS-MOTOR ACA 63 B 6 /HE

IE2AC06B6002

General data

| | |
|--------------------------|-------------------------------|
| Type of motor | 3~ |
| Type designation | ACA |
| Frame size | 63 |
| Mounting | B3 |
| Frame material | Aluminium |
| Insulationclass | F/B |
| Terminal box location | top DE |
| Terminal box orientation | cable gland to the right side |
| Weight (kg) | 5.5 |
| Rotation Direction | right /left |
| Vibration level | A |
| Balancing method | half key |
| cooling type | IC411 |
| Executed acc. to | IEC 60034-1 |
| noise level | IEC 60034-9 |

Influential factors

| | |
|--------------------------|---------------|
| Duty | S1 |
| Ambient temperature (°C) | -20 up to +40 |
| Height of location (m) | 1000 |

Electrical specification

| | |
|---------------------------------|------------|
| Power 1 50Hz (kW) | 0.12 |
| Power 1 60Hz (kW) | 0.12 |
| Frequency (Hz) | 50/60 |
| Voltage 50Hz (V) | 230/400 |
| Voltage 60Hz (V) | 265/460 |
| Voltage tolerance | +/-10% |
| Connection | Δ/Y |
| Poles | 6 |
| Efficiency 100% 50Hz (%) | 50,6 |
| Efficiency 75% 50Hz (%) | 50,6 |
| Efficiency 50% 50Hz (%) | 49,6 |
| Efficiency 100% 60Hz (%) | 50,5 |
| Efficiency 75% 60Hz (%) | 50,6 |
| Efficiency 50% 60Hz (%) | 49,6 |
| Power factor | 0,6 |
| Starting current factor (Ia/In) | 4,4 |
| Starting torque factor (Ma/Mn) | 2 |
| Breakdown torque (Mk/Mn) | 2,1 |
| Rated current 50Hz (A) | 0,99/0,57 |
| Rated current 60Hz (A) | 0,87/0,50 |
| Eff.Cl.50Hz | IE2 |
| Eff.Cl.60Hz | IE2 |

Mechanical data

| | |
|---------------------------|---------------|
| Torque (Nm) | 1,35/1,12 |
| Rotation speed (1/min) | 850/1020 |
| Bearing DE | 6201.ZZ.C3 |
| Bearing NDE | 6201.ZZ.C3 |
| Mounting of bearing DE | loose bearing |
| Mounting of bearing NDE | loose bearing |
| Bearing lifetime (h) | 20000 |
| allow. Radial load (X/2) | 375 |
| allow. Radial load (X0) | 400 |
| allow. Radial load (Xmax) | 350 |
| allow. Axial load | 350 |
| allow. Axial load (V1) | 335 |

Motor properties

| | |
|-------------------------------------|------------------------|
| Color | RAL7030 |
| Paint surface | shiny |
| Protection class | IP55 |
| Cable gland size (cable connection) | 1xM20x1,5 1xblind plug |
| Cable gland type | Standard |
| Shaft end (mm) | 11 x 23 |
| Shaft material | C45 |
| Specification NDE | Plastic fan |