

## THREE-PHASE-ASYNCHRONOUS-MOTOR ACA 71 A 4 /HE

IE2AC07A4001

### General data

Type of motor	3~
Type designation	ACA
Frame size	71
Mounting	B3
Frame material	Aluminium
Insulationclass	F/B
Terminal box location	top DE
Terminal box orientation	cable gland to the right side
Weight (kg)	6,4
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to	IEC 60034-1
noise level	IEC 60034-9

### Influential factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

### Electrical specification

Power 1 50Hz (kW)	0,25
Power 1 60Hz (kW)	0,25
Frequency (Hz)	50/60
Voltage 50Hz (V)	230/400
Voltage 60Hz (V)	265/460
Voltage tolerance	+/-10%
Connection	$\Delta/Y$
Poles	4
Efficiency 100% 50Hz (%)	68,5
Efficiency 75% 50Hz (%)	68,5
Efficiency 50% 50Hz (%)	67,1
Efficiency 100% 60Hz (%)	70,0
Power factor	0,74
Starting current factor (Ia/In)	5,2
Starting torque factor (Ma/Mn)	2,1
Breakdown torque (Mk/Mn)	2,2
Rated current 50Hz (A)	1,24/0,71
Rated current 60Hz (A)	1,05/0,61
Eff.Cl.50Hz	IE2
Eff.Cl.60Hz	IE2

### Mechanical data

Torque (Nm)	1,79/1,49
-------------	-----------

### Mechanical data

Rotation speed (1/min)	1335/1602
Bearing DE	6202.ZZ.C3
Bearing NDE	6202.ZZ.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	loose bearing
Bearing lifetime (h)	20000
allow. Radial load (X/2)	412,5
allow. Radial load (X0)	450
allow. Radial load (Xmax)	375
allow. Axial load	400
allow. Axial load (V1)	380

### Motor properties

Color	RAL7030
Paint surface	shiny
Protection class	IP55
Cable gland size (cable connection)	1xM20x1,5 1xblind plug
Cable gland type	Standard
Shaft end (mm)	14 x 30
Shaft material	C45
Specification NDE	Plastic fan