

THREE-PHASE-ASYNCHRONOUS-MOTOR ACA 63 A 2 /HE

IE2AC06A2001

General data

Type of motor	3~
Type designation	ACA
Frame size	63
Mounting	B3
Frame material	Aluminium
Insulationclass	F/B
Terminal box location	top DE
Terminal box orientation	cabl gland to the right side
Weight (kg)	5.1
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to	IEC 60034-1
noise level	IEC 60034-9

Influential factors

Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Electrical specification

Power 1 50Hz (kW)	0.18
Power 1 60Hz (kW)	0.18
Frequency (Hz)	50/60
Voltage 50Hz (V)	230/400
Voltage 60Hz (V)	265/460
Voltage tolerance	+/-10%
Connection	Δ/Y
Poles	2
Efficiency 100% 50Hz (%)	60,4
Efficiency 75% 50Hz (%)	60,4
Efficiency 50% 50Hz (%)	59,2
Efficiency 100% 60Hz (%)	64
Power factor	0,8
Starting current factor (Ia/In)	5,5
Starting torque factor (Ma/Mn)	2,2
Breakdown torque (Mk/Mn)	2,2
Rated current 50Hz (A)	0,94/0,54
Rated current 60Hz (A)	0,78/0,45
Eff.Cl.50Hz	IE2
Eff.Cl.60Hz	IE2

Mechanical data

Torque (Nm)	0,63/0,53
-------------	-----------

Mechanical data

Rotation speed (1/min)	2725/3270
Bearing DE	6201.ZZ.C3
Bearing NDE	6201.ZZ.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	loose bearing
Bearing lifetime (h)	20000
allow. Radial load (X/2)	300
allow. Radial load (X0)	325
allow. Radial load (Xmax)	275
allow. Axial load	250
allow. Axial load (V1)	235

Motor properties

Color	RAL7030
Paint surface	shiny
Protection class	IP55
Cable gland size (cable connection)	1xM20x1,5 1xblind plug
Cable gland size (option)	M16x1,5
Cable gland type	Standard
Shaft end (mm)	11 x 23
Shaft material	C45
Specification NDE	Plastic fan

Additional option

Protection winding	PTC 150°C
--------------------	-----------